

**Weierstraß-Institut**  
**für Angewandte Analysis und Stochastik**  
**Leibniz-Institut im Forschungsverbund Berlin e. V.**

Preprint

ISSN 2198-5855

**A rate-independent gradient system in damage  
coupled with plasticity via structured strains**

Elena Bonetti<sup>1</sup>, Elisabetta Rocca<sup>2,3</sup>, Riccarda Rossi<sup>4</sup>, Marita Thomas<sup>2</sup>

submitted: November 16, 2015

<sup>1</sup> Dipartimento di Matematica  
Università degli Studi di Pavia  
Via Ferrata 1  
I-27100 Pavia  
Italy  
E-Mail: elena.bonetti@unipv.it

<sup>2</sup> Weierstrass Institute  
Mohrenstr. 39  
10117 Berlin  
Germany  
E-Mail: elisabetta.rocca@wias-berlin.de  
marita.thomas@wias-berlin.de

<sup>3</sup> Dipartimento di Matematica  
Università degli Studi di Milano  
Via Saldini 50  
I-20133 Milano  
Italy  
E-Mail: elisabetta.rocca@unimi.it

<sup>4</sup> DIMI  
Università di Brescia  
Via Branze 38  
I-25100 Brescia  
Italy  
E-Mail: riccarda.rossi@unibs.it

No. 2178  
Berlin 2015



---

2010 *Mathematics Subject Classification.* 74C05, 74E10, 74R05, 74R20, 49S05, 49J40, 35K86.

*Key words and phrases.* Rate-independent systems, tensorial damage model, anisotropic damage, plasticity, structured strain, energetic solutions, existence results.

The work of Elisabetta Rocca was supported by the FP7-IDEAS-ERC-StG Grant #256872 (EntroPhase), by GNAMPA (Gruppo Nazionale per l'Analisi Matematica, la Probabilità e le loro Applicazioni) of INdAM (Istituto Nazionale di Alta Matematica). Elena Bonetti and Riccarda Rossi were partially supported by a MIUR-PRIN'10-'11 grant for the project "Calculus of Variations", and by GNAMPA (Gruppo Nazionale per l'Analisi Matematica, la Probabilità e le loro Applicazioni) of INdAM (Istituto Nazionale di Alta Matematica), and by IMATI – C.N.R. Pavia. Marita Thomas was partially supported by the German Research Foundation (DFG) within CRC 1114, project C05.

Edited by  
Weierstraß-Institut für Angewandte Analysis und Stochastik (WIAS)  
Leibniz-Institut im Forschungsverbund Berlin e. V.  
Mohrenstraße 39  
10117 Berlin  
Germany

Fax: +49 30 20372-303  
E-Mail: [preprint@wias-berlin.de](mailto:preprint@wias-berlin.de)  
World Wide Web: <http://www.wias-berlin.de/>

ABSTRACT. This contribution deals with a class of models combining isotropic damage with plasticity. It has been inspired by a work by Freddi and Royer-Carfagni [FRC10], including the case where the inelastic part of the strain only evolves in regions where the material is damaged. The evolution both of the damage and of the plastic variable is assumed to be rate-independent. Existence of solutions is established in the abstract energetic framework elaborated by Mielke and coworkers (cf., e.g., [Mie05, Mie11b]).

## INTRODUCTION

It is well known that damage in a material can be interpreted as a degradation of its elastic properties due to the failure of its microscopic structure. Such macroscopic mechanical effects take their origin from the formation of micro-cracks and cavities at a microscopic scale. Macroscopically, these degeneracy effects may be described by the incorporation of an internal variable into the model, the damage parameter, which in particular features a decrease of stiffness with ongoing damage. However, some materials show a more complex behavior, possibly presenting different responses to traction and compression loading, or exhibiting some plastic-like behavior when the damage process is activated.

The study of plastic material behavior at small strains in itself has a long tradition, cf. e.g. [Hil50, Lub90], and numerous analytical and numerical results exist, cf. e.g. [Tem85, HR99, RDG08, Kne09, Kne10, JRZ13, BMR12, BR08, DMS14, DMDMM08, DMDM06]. Also isotropic damage in itself nowadays is a well-investigated phenomenon and it has been treated in the spirit of phase-field theories from the point of view of modeling, analysis, and computations, cf. e.g. [FN96, BS04, BSS05, MR06, TM10, AKS10, KRZ13, FG06, GL09, MRZ10, JZ15, Gia05, PM13, DMI13]. In this family of models, a scalar internal variable is introduced to denote the local proportion of active micro-bonds vs. the damaged ones. Nonetheless, this approach does not permit to distinguish different anisotropic behaviors and the appearance of an unknown transformation strain, as it occurs in plasticity. Thus, it is of some interest to combine scalar and tensorial variables to describe both of these two effects.

More precisely, in this contribution, we assume that a “transition strain”, a *structured strain* as it is called in [FRC10], may appear and evolve during the damage process. The latter in itself decreases the stiffness of the material during its evolution. The first effect makes our model akin to a plasticity model, in which the plastic strain is activated through damage and its norm depends on the damage level; we refer to [AMV14] for an alternative model for damage coupled with plasticity, recently analyzed in [Cri, CL15]. As a consequence, we deal with two internal variables: a scalar one  $\chi$ , standardly denoting the local proportion of active bonds in the micro-structure of the material, and a tensorial one  $D$ , which stands for the transformation strain arising during the damage evolution. The behavior of these two variables is recovered by a generalization of the principle of virtual powers, in which micro-forces responsible for the formation of micro-cracks and micro-slips are included; we confine the discussion to the small-strain regime and the isothermal case, though. The momentum balance equation for the displacement  $\mathbf{u}$  is eventually written in the quasi-static case, while the evolution of the internal variables  $\chi$  and  $D$  is governed by an energy functional and a 1-homogeneous dissipation potential, leading to a rate-independent evolution of these variables and possibly including irreversibility constraints.

All in all, the resulting PDE system in the variable  $\mathbf{q} = (\mathbf{u}, \chi, D)$  pertains to the class of abstract gradient systems of the form

$$(0.1) \quad \partial\mathcal{R}(\mathbf{q}_t) + D\mathcal{E}(t, \mathbf{q}(t)) \ni 0 \quad \text{in } (0, T),$$

driven by an energy functional  $\mathcal{E}$  and a dissipation potential  $\mathcal{R}$ , positively homogeneous of degree 1 and only acting on the dissipative variables  $(\chi, D)$ . For the analysis of this system, we will resort to the *energetic formulation* for rate-independent systems developed by Mielke and coworkers, cf. [MT04, Mie05, MM05, Mie11b]. We will thus prove the existence of energetic solutions by applying an abstract existence result from [Mie11b].

**Plan of the paper.** The derivation of the model will be carried out in Section 1. The precise mathematical assumptions are collected in Section 2. The existence theorem (Thm. 3.4) is stated in Section 3 in the framework of energetic solutions. Finally, its proof is carried out in Section 4.

## 1. CONTINUUM MECHANICAL DERIVATION OF THE MODEL

Along a time-interval  $[0, T]$ , we study the mechanical behavior of a body, occupying a domain  $\Omega \subset \mathbb{R}^d$ ,  $1 < d \in \mathbb{N}$ . The body is exposed to time-dependent external loadings, which possibly cause a degradation of the micro-structure of the material, leading to inelastic responses. In particular, we restrict ourselves to a small-strain regime and introduce the vector  $\mathbf{u}$  of small displacements. Hence, as already mentioned in the introduction, we shall formulate the model in terms of the strain and in terms of two further state variables  $\chi : [0, T] \times \Omega \rightarrow [0, 1]$  and  $D : [0, T] \times \Omega \rightarrow \mathbb{R}^{d \times d}$ , which are internal variables more specifically related to the description of damage and plastic-like behavior. Accordingly, in view of the conjugate approach, the free energy will depend on the strain and on these two internal variables, and the stress shall be derived in terms of them.

In particular, using the approach of [FRC10], we first suppose that the symmetric gradient of the displacement  $\mathbf{u}$

$$e(\mathbf{u}) = (\nabla \mathbf{u} + \nabla^\top \mathbf{u})/2$$

is decomposed in two parts:

$$(1.1) \quad e(\mathbf{u}) = E_{\text{el}} + \Xi$$

where  $E_{\text{el}} \in \mathbb{R}^{d \times d}$  represents the *elastic* part of the strain and  $\Xi \in \mathbf{S} \subset \mathbb{R}^{d \times d}$  the *inelastic* one, associated with the formation of micro-cracks or micro-slips. It is indeed known that (see, e.g., [Kac90, Fré02]) for an inelastic body the strain is determined by the stress and by some additional (internal) variable, which may be interpreted within the framework of a general plasticity theory. In this spirit, the set  $\mathbf{S} \subset \mathbb{R}^{d \times d}$  can, e.g., be the subspace of symmetric matrices or, as in plasticity theory, the subspace of deviatoric (i.e., trace-free)  $\mathbb{R}^{d \times d}$ -matrices. In order to allow for the treatment of different types of inelastic phenomena we keep  $\mathbf{S} \subset \mathbb{R}^{d \times d}$  general, and refer to Remark 1.2 below for more details on specific choices of  $\mathbf{S}$  and their meaning.

In the context of this damage model, we prescribe that the inelastic part of the strain depends on the state of the internal bonds acting at a microscopic level in the material. We also assume that the phenomenon of damage is *progressive*, in the sense that within the same body there may be regions where the material is completely damaged and regions where the microstructure is lost, but not yet failed. As it is common in the modeling of isotropic damage, the variable  $\chi$  is therefore linked to the proportion of active or inactive bonds in a neighborhood of material-dependent size (representative volume element) centered around any material point  $x \in \Omega$ . Hence,  $\chi$  takes values in the interval  $[0, 1]$ . Throughout this work we will assume that  $\chi$  stands for the proportion of *active bonds* at the micro scale in the material, thus, with the value 1 in the sound regions and 0 in a failed zone. Along the footsteps of [FRC10] (cf. Remark 1.2 later on), we introduce a second internal variable  $D \in \mathbf{S}$  of type “transformation” strain leading to plastic effects and developing in the regions where the material is damaged; it shall hereafter be formally referred to as *plastic strain*. Thus, following [FRC10], the inelastic part of the strain is a function of  $\chi$  and  $D$ ,

$$(1.2) \quad \Xi : [0, 1] \times \mathbf{S} \rightarrow \mathbf{S} \quad \text{s.t.} \quad \Xi(1, D) = 0 \text{ and } \Xi(0, D) = D \quad \text{for every } D \in \mathbf{S}.$$

As a particular choice for the function  $\Xi$  one may consider

$$(1.3) \quad \Xi(\chi, D) = (1 - \chi)D.$$

But as a general feature of  $\Xi$ , note that, in view of (1.1), for  $\chi = 1$  we have  $E_{\text{el}} = e(\mathbf{u})$ , whereas for  $\chi = 0$  we have  $E_{\text{el}} = e(\mathbf{u}) - D$ .

Following the continuum-mechanical modeling perspective of Frémond, cf. e.g. [Fré02], we shall now introduce the constitutive functionals and equations specifying the damage-plasticity model under consideration. Let us point out that this approach is mainly based on a variational principle, i.e. the (generalized) principle of virtual powers. The main idea is that forces acting at a

microscopic level in the material, responsible for the formation of micro-cracks and thus activating damage, have to be included in the whole energy balance of the mechanical system. Hence, as a prerequisite we shall postulate that the powers of the interior forces  $P_i$ , the exterior forces  $P_e$ , and the acceleration forces  $P_a$ , acting on the elasto-plastic and damageable body, occupying the (reference) domain  $\Omega \subset \mathbb{R}^d$ , are balanced, i.e.,

$$(1.4) \quad P_i + P_e = P_a \quad \text{and, here, } P_a = 0,$$

as we will confine our discussion to a quasistatic evolution.

**The principle of virtual powers.** The principle of virtual powers now postulates that the above balance of powers has to hold on any subdomain  $\omega \subset \Omega$ , thus leading to the *virtual powers* of this subdomain, which are assumed to be given in integral form by

$$P_e(\omega) = \int_{\omega} p_e \, dx + \int_{\partial\omega} \tilde{p}_e \, dS \quad \text{and} \quad P_i(\omega) = \int_{\omega} p_i \, dx.$$

Consequently, different kinds of virtual velocities are introduced: macroscopic velocities  $\mathbf{v}$ , microscopic scalar velocities  $\gamma$ , and microscopic tensorial velocities  $V$ . Under the assumption that no external forces act on the microscopic level, we can prescribe the virtual external power  $P_e$  of the subdomain  $\omega \subset \Omega$  in the form

$$(1.5) \quad P_e(\omega) = \int_{\omega} \mathbf{f} \cdot \mathbf{v} \, dx + \int_{\partial\omega} \mathbf{t} \cdot \mathbf{v} \, dS$$

for any macroscopic virtual velocity  $\mathbf{v} : \omega \rightarrow \mathbb{R}^d$  and for the given volumetric force  $\mathbf{f} : \omega \rightarrow \mathbb{R}^d$  and the given surface force  $\mathbf{t} : \partial\omega \rightarrow \mathbb{R}^d$  acting on  $\omega \subset \Omega$ . Similarly, the virtual internal power of  $\omega$  is given in integral form as the product of the internal forces and virtual velocities. Due to the fact that the body is exposed to elasto-plastic deformations and damage, the internal forces consist of the macroscopic stress  $\sigma : \Omega \rightarrow \mathbb{R}^{d \times d}$  and additional internal micro-stresses  $B : \omega \rightarrow \mathbb{R}$ ,  $\mathbf{H} : \omega \rightarrow \mathbb{R}^d$ ,  $X : \omega \rightarrow \mathbb{R}^{d \times d}$ , and  $\mathbf{Y} : \omega \rightarrow \mathbb{R}^{d^3}$  related to damage and the plastic deformation. In what follows, the symbols  $:$  and  $::$  stand for the products in the spaces of  $d^2$ - and  $d^3$ -tensors, respectively. For any macroscopic virtual velocity  $\mathbf{v}$ , for all microscopic velocities  $\gamma : \omega \rightarrow \mathbb{R}$ , and for all microscopic tensorial velocities  $V : \omega \rightarrow \mathbf{S}$ , the virtual internal power of  $\omega$  is thus given by

$$(1.6) \quad P_i(\omega) = \int_{\omega} p_i \, dx = - \int_{\omega} (\sigma : \epsilon(\mathbf{v}) + B\gamma + \mathbf{H} : \nabla\gamma + X : V + \mathbf{Y} :: \nabla V) \, dx.$$

Observe that the definition of  $p_i$  reflects the fact that the power of the interior forces is zero for any (macroscopic) rigid motion.

Now, taking into account that the relations (1.4)–(1.6) shall hold for any subdomain  $\omega \subset \Omega$  and for any virtual velocity, the resulting balance equations are

$$(1.7a) \quad -\operatorname{div} \sigma = \mathbf{f} \quad \text{in } \Omega, \quad \sigma \mathbf{n} = \mathbf{t} \quad \text{on } \partial\Omega,$$

$$(1.7b) \quad B - \operatorname{div} \mathbf{H} = 0 \quad \text{in } \Omega, \quad \mathbf{H} \cdot \mathbf{n} = 0 \quad \text{on } \partial\Omega,$$

$$(1.7c) \quad X - \operatorname{div} \mathbf{Y} = 0 \quad \text{in } \Omega, \quad \mathbf{Y} \cdot \mathbf{n} = 0 \quad \text{on } \partial\Omega.$$

**The constitutive relations.** Following [Fré02, Chap.s 3, 4], we assume that the constitutive relations are comprised in two functionals, the free energy functional  $\mathcal{F}$  and the pseudo-potential of dissipation  $\mathcal{R}$  in integral form, with densities  $\Psi$  and  $\Phi$ , respectively:

$$(1.8) \quad \mathcal{F}(\mathbf{u}, \chi, D) := \int_{\Omega} \Psi \, dx \quad \text{and} \quad \mathcal{R}(\dot{\chi}, \dot{D}) := \int_{\Omega} \Phi \, dx.$$

Formally using the above localization arguments, and in view of (1.7), we prescribe the following constitutive relations

$$(1.9) \quad \sigma = \frac{\partial \Psi}{\partial \epsilon}, \quad B = \frac{\partial \Phi}{\partial \chi_t} + \frac{\partial \Psi}{\partial \chi}, \quad \mathbf{H} = \frac{\partial \Psi}{\partial \nabla \chi}, \quad X = \frac{\partial \Phi}{\partial D_t} + \frac{\partial \Psi}{\partial D}, \quad \mathbf{Y} = \frac{\partial \Psi}{\partial \nabla D}.$$

**Choice of the constitutive functions.** We choose the density of the pseudo-potential of dissipation of the form

$$(1.10) \quad \begin{aligned} \Phi(D_t, \chi_t) &:= R_{\text{inel}}(D_t) + R_{\text{dam}}(\chi_t), \quad \text{where} \\ R_{\text{inel}}(D_t) &:= \mu|D_t| \quad \text{and} \quad R_{\text{dam}}(\chi_t) := \nu|\chi_t| + I_{(-\infty, 0]}(\chi_t) \end{aligned}$$

for material parameters  $\mu, \nu > 0$ . Note that both  $R_{\text{inel}}$  and  $R_{\text{dam}}$  are positively 1-homogeneous, thus featuring a rate-independent evolution of the variables  $D$  and  $\chi$ . In particular, for the definition of  $R_{\text{dam}}$ , observe that the indicator term  $I_{(-\infty, 0]}$  enforces the unidirectionality constraint  $\chi_t \leq 0$ , i.e. that the parameter  $\chi$  is a non-increasing function of time, ensuring that damage can only increase. In turn, the free energy density  $\Psi$  shall feature an indicator term acting on  $\chi$ , cf. (1.13), which forces the  $\chi$ -component of the solution to the evolutionary system we shall derive to take positive values. Starting from an initial datum  $\chi_0$  with  $\chi_0(x) \in [0, 1]$  for almost all  $x$  in  $\Omega$ , we will thus obtain that  $\chi(x, t) \in [0, 1]$  for almost all  $(x, t) \in \Omega \times [0, T]$ , in accordance with the physical meaning of  $\chi$  as a *proportion* of active bonds.

For the definition of the free energy density  $\Psi$  we assume, in the spirit of linear elasticity, that  $\Psi$  consists of a quadratic elastic contribution, a coupling term  $H$ , and terms  $J$  and  $G$  also featuring regularizations for the damage variable and the plastic strain, respectively. In particular,  $\Psi$  shall take the following form:

$$(1.11) \quad \begin{aligned} \Psi(e(\mathbf{u}), \chi, D, \nabla\chi, \nabla D) &:= \frac{1}{2}(e(\mathbf{u}) - \Xi(\chi, D)) : \mathbb{K}(\chi) : (e(\mathbf{u}) - \Xi(\chi, D)) \\ &\quad + H(\chi, D) + J(\chi, \nabla\chi) + G(D, \nabla D). \end{aligned}$$

Here,  $\Xi : \mathbb{R} \times \mathbb{R}^{d \times d} \rightarrow \mathbb{R}^{d \times d}$  is defined as in (1.2). Moreover, as usual in damage models we consider a  $\chi$ -dependent stiffness tensor  $\mathbb{K}$ , such that  $\mathbb{K}(\chi)$  is a symmetric  $\mathbb{R}^{d^4}$ -tensor for every  $\chi$ , with the property that a decrease of the value of  $\chi$  leads to a decrease of the quadratic contribution of the energy term. In principle, with the choice of  $\mathbb{K}$  we can incorporate in the model both the case in which the stiffness degenerates when the material is completely damaged (i.e., for  $\chi = 0$ , the tensor  $\mathbb{K}(0)$  is no longer positive definite, in particular it might happen that  $\mathbb{K}(0) = 0$ , cf. e.g. [BMR09, MRZ10, Mie11a, HK15]), and the case in which some residual stiffness is guaranteed even for  $\chi = 0$  (i.e.,  $\mathbb{K}(\chi)$  is positive definite for every  $\chi$ ). In fact, in what follows we shall confine our analysis to the latter case.

The coupling term  $H$  shall take into account different cohesive properties of the material and the plastic behavior. A possible choice could be

$$(1.12) \quad H(\chi, D) = w(1 - \chi) + \frac{1}{2}|D|^2(1 - \chi) \quad \text{with } w > 0.$$

Observe that, if the material is completely undamaged, i.e.  $\chi = 1$ , the term  $H$  plays the role of a cohesion energy while, in the case  $\chi = 0$ , i.e. when the material is maximally ‘‘broken’’, it leads to a hardening effect for the plasticity variable  $D$ , since  $w > 0$ .

The function  $J$  for the damage variable shall guarantee the modeling assumption  $\chi \in [0, 1]$  a.e. in  $\Omega$  introducing some internal constraint. A possible choice would be

$$(1.13) \quad J(\chi, \nabla\chi) := I_{[0, 1]}(\chi) + \frac{\alpha}{2}|\nabla\chi|^2 + W_1(\chi).$$

**Remark 1.1.** Let us point out that, setting  $W_1(\chi) = \frac{1}{\alpha}(1 - \chi)^2$  with small  $\alpha > 0$  would rather inhibit damage. However, we may allow also for non-convex choices of  $W_1$ , e.g. in terms of a double-well potential. As analyzed in [Tho13] in the context of brittle damage, the choice  $W_1(\chi) = \frac{1}{\alpha}\chi^2(1 - \chi)^2$  with small  $\alpha > 0$  will yield that  $\chi \in \{0, 1\}$  a.e. in  $\Omega$  as  $\alpha \rightarrow 0$ , thus accounting only for the sound and the maximally damaged state of the material in the limit.

In the same manner, the term  $G$  may confine the plastic strain to a closed, convex subset  $K$  of the subspace  $\mathbf{S} \subset \mathbb{R}^{d \times d}$ ; we refer to Remark 1.2 for different choices of  $K$  and  $\mathbf{S}$ . As a possible form of  $G$  we may consider

$$(1.14) \quad G(D, \nabla D) := I_K(D) + (|D|^2 - 1)^2 + \frac{1}{q}|\nabla D|^q \quad \text{with } q \in (1, \infty).$$

**Remark 1.2** (Comparison with [FRC10] and possible choices of  $\mathbf{S}$  and  $K$ ). In [FRC10], following [DPO93] the authors refer to  $\Xi$  as the *structured strain*, and postulate for it the form (1.3) as a

function of  $D$ , which, as a function of  $x \in \Omega$ , in turn represents the *structured strain* that would develop in a neighbourhood of  $x$  if the material was completely disgregated. In [FRC10] it is in fact remarked that the form of the field  $D = D(x)$  may depend upon the material microstructure and the local defects of the body, so that its complete characterization is an open problem. Hence, the authors propose a *mesoscopic representation* for  $D$  as a function of  $e(\mathbf{u})$ .

More precisely, the relation between  $D$  and  $e(\mathbf{u})$  is established through the minimization of the quadratic elastic energy (i.e. the first term in (1.11)), for  $\chi = 0$ , over suitable classes of admissible structured strains. This reflects the fact that  $D$  physically represents the strain that a completely disgregated body may attain without energy consumption in order to accommodate the boundary data. Different choices for the class  $\mathbf{S}$  of admissible strains lead to models with different types of material responses to damage and fractures.

For example, taking  $\mathbf{S}$  as the space of all symmetric tensors it is possible to recover a model describing the formation of *cleavage fractures*, viz. fractures directly proportional to the macroscopic deformation. Indeed, minimizing the elastic contribution to the free energy in (1.11) for  $\chi = 0$ , in the case in which  $\mathbb{K}(0)$  is positive definite, leads to  $D = e(\mathbf{u})$ . Observe that, when  $D = e(\mathbf{u})$  we recover the original form of the elastic part in the free energy

$$\frac{1}{2}(e(\mathbf{u}) - (1 - \chi)D) : \mathbb{K}(\chi) : (e(\mathbf{u}) - (1 - \chi)D) = \frac{1}{2}\chi^2|e(\mathbf{u})|^2.$$

Setting  $\mathbf{S}$  as the space of symmetric tensors with null deviatoric part (i.e., *trace-free* matrices) brings to a model for the formation of less brittle fractures, like those occurring in materials like stones. In this connection, as common in plasticity models (cf. e.g. [HR99]), we might choose  $K \subset \mathbf{S}$  as a closed and convex subset of the set of deviatoric matrices  $\mathbf{S}$ .

**The final set of constitutive equations.** Combining in (1.7a)-(1.7c) the constitutive relations (1.9) with (1.10) and (1.11) we obtain the set of constitutive equations, to be satisfied in  $\Omega \times (0, T)$ :

$$\begin{aligned} (1.15a) \quad & -\operatorname{div}(\mathbb{K}(\chi) : (e(\mathbf{u}) - \Xi(\chi, D))) = \mathbf{f}, \\ (1.15b) \quad & \partial R_{\text{dam}}(\chi_t) + \partial_\chi J(\chi, \nabla \chi) - \operatorname{div} \frac{\partial J(\chi, \nabla \chi)}{\partial(\nabla \chi)} \\ & \ni -\frac{1}{2}(e(\mathbf{u}) - \Xi(\chi, D)) : \mathbb{K}'(\chi) : (e(\mathbf{u}) - \Xi(\chi, D)) \\ & + (e(\mathbf{u}) - \Xi(\chi, D)) : \mathbb{K}(\chi) : \frac{\partial \Xi(\chi, D)}{\partial \chi} - \frac{\partial H(\chi, D)}{\partial \chi}, \\ (1.15c) \quad & \partial R_{\text{inel}}(D_t) + \partial_D G(D, \nabla D) - \operatorname{div} \frac{\partial G(D, \nabla D)}{\partial(\nabla D)} \\ & - \mathbb{K}(\chi) (e(\mathbf{u}) - \Xi(\chi, D)) : \frac{\partial \Xi(\chi, D)}{\partial D} + \frac{\partial H(\chi, D)}{\partial D} \ni 0 \end{aligned}$$

with  $\mathbf{f}$  the volume force from (1.5). We shall assume that the inelastic stress function  $\Xi$  and the material tensor  $\mathbb{K}$  are suitably smooth. We will supplement the rate-independent system (1.15) with the boundary conditions

$$(1.16) \quad \begin{aligned} \mathbf{u}(x, t) &= \mathbf{u}_D(t) \text{ on } \Gamma_D, & \mathbb{K}(\chi) : (e(\mathbf{u}(x, t)) - \Xi(\chi, D))\mathbf{n} &= \mathbf{t} \text{ on } \Gamma_N, \\ \frac{\partial \chi}{\partial \mathbf{n}} &= 0 \text{ in } \partial\Omega \times (0, T), & \frac{\partial D}{\partial \mathbf{n}} &= 0 \text{ in } \partial\Omega \times (0, T), \end{aligned}$$

with  $\Gamma_D$  and  $\Gamma_N$  the Dirichlet and the Neumann parts of the boundary  $\partial\Omega$ , respectively, and  $\mathbf{n}$  the outward unit normal to  $\partial\Omega$ . In what follows, we will address the existence of solutions to the boundary-value problem (1.15)–(1.16) in a suitably weak sense. We will discuss a suitable solution concept in Section 3 ahead.

**Remark 1.3.** Let us point out that system (1.15) is related, for special choices of the involved functionals, to well-known models in plasticity and phase transitions processes. Indeed, taking, for example,

$$\mathbb{K}(\chi) = \operatorname{Id} \in \mathbb{R}^{d^4}, \quad \Xi(\chi, D) = (1 - \chi)D, \quad \text{and} \quad H(\chi, D) = w(1 - \chi) + \frac{1}{2}|D|^2(1 - \chi),$$

we get the following PDE system in  $\Omega \times (0, T)$

$$(1.17a) \quad -\operatorname{div}(e(\mathbf{u}) - (1 - \chi)D) = \mathbf{f},$$

$$(1.17b) \quad \begin{aligned} & \partial R_{\text{dam}}(\chi_t) + \partial_\chi J(\chi, \nabla \chi) - \operatorname{div} \frac{\partial J(\chi, \nabla \chi)}{\partial(\nabla \chi)} \\ & \ni -\frac{1}{2}|e(\mathbf{u}) - (1 - \chi)D|^2 - D : (e(\mathbf{u}) - (1 - \chi)D) + \frac{1}{2}|D|^2 + w, \end{aligned}$$

$$(1.17c) \quad \begin{aligned} & \partial R_{\text{inel}}(D_t) + \partial_D G(D, \nabla D) - \operatorname{div} \frac{\partial G(D, \nabla D)}{\partial(\nabla D)} \\ & - (e(\mathbf{u}) - (1 - \chi)D) : (1 - \chi) + (1 - \chi)D \ni 0. \end{aligned}$$

In particular, without terms as  $J$  and  $G$  in the free energy, the resulting equations correspond to a rate independent evolution for the parameter  $\chi$ , governed by a quadratic source of damage (including strain and structured/plasticity strain), and a plasticity equation with hardening contribution (obtained by the third equation in the case  $\chi = 0$ ).

## 2. ASSUMPTIONS AND NOTATION

In the following, given a Banach space  $\mathbf{B}$ , we shall denote by  $\mathbf{B}^*$  its dual space, by  $\|\cdot\|_{\mathbf{B}}$  its norm, and by  $\langle \cdot, \cdot \rangle_{\mathbf{B}}$  the duality pairing between  $\mathbf{B}^*$  and  $\mathbf{B}$ . We set  $R_\infty := \mathbb{R} \cup \{+\infty\}$ .

In the next lines, we specify the mathematical assumptions for the quantities introduced so far.

**Assumptions on the domain:** We assume that

$$(2.1) \quad \begin{aligned} & \Omega \subset \mathbb{R}^d, \quad d \in \mathbb{N}, \text{ is a bounded domain with Lipschitz-boundary } \partial\Omega \text{ such that} \\ & \Gamma_D \subset \partial\Omega \text{ is nonempty and relatively open and } \Gamma_N := \partial\Omega \setminus \Gamma_D. \end{aligned}$$

**Function spaces:** We fix the function spaces as follows

$$(2.2a) \quad \mathbf{U} := \{u \in H^1(\Omega, \mathbb{R}^d), u = 0 \text{ on } \Gamma_D\},$$

$$(2.2b) \quad \mathbf{Z} := L^1(\Omega),$$

$$(2.2c) \quad \mathbf{M} := \{z \in \mathbf{Z}, z \in [0, 1] \text{ a.e. in } \Omega\},$$

$$(2.2d) \quad \mathbf{X} := \{z \in W^{1,r}(\Omega)\}, \quad r > 1,$$

$$(2.2e) \quad \mathbf{V} := L^1(\Omega; \mathbb{R}^{d \times d}),$$

$$(2.2f) \quad \mathbf{H} := W^{1,q}(\Omega; \mathbf{S}), \quad q \geq 2d/(d+2),$$

$$(2.2g) \quad \mathbf{H}_1 := L^{q_1}(\Omega; \mathbf{S}), \quad q_1 \geq \max\{q, 2\},$$

and we recall that  $\mathbf{S}$  is a subspace of  $\mathbb{R}^{d \times d}$ . With (2.7c) ahead we shall further specify the conditions on the indices  $q$  and  $q_1$ .

**Assumptions on the given data:** Given  $\mathbf{U}$  from (2.2a), we shall assume that the volume forces  $\mathbf{f}$  and the surface forces  $\mathbf{t}$  from (1.5) are comprised in a time-dependent functional  $F : [0, T] \rightarrow \mathbf{U}^*$ . Moreover, for all  $t \in [0, T]$ , we suppose that the Dirichlet datum  $\mathbf{u}_D(t)$  has an extension from  $\Gamma_D$  into the domain  $\Omega$ , also denoted by  $\mathbf{u}_D(t)$ . In particular, we make the following regularity assumptions:

$$(2.3a) \quad \begin{aligned} & F \in C^1([0, T]; \mathbf{U}^*) \text{ comprises both volume forces and Neumann data,} \\ & \text{such that } \|F\|_{C^1([0, T]; \mathbf{U}^*)} \leq C_F, \end{aligned}$$

$$(2.3b) \quad \begin{aligned} & \mathbf{u}_D \in C^1([0, T]; \mathbf{U}) \text{ is an extension of the Dirichlet datum,} \\ & \text{such that } \|\mathbf{u}_D\|_{C^1([0, T]; \mathbf{U})} \leq C_D \text{ and } e_D := e(\mathbf{u}_D). \end{aligned}$$

Furthermore, for the elastic tensor  $\mathbb{K} : [0, 1] \rightarrow \mathbb{R}^{d \times d}$  we assume symmetry and positive definiteness, i.e.,

$$(2.3c) \quad \begin{aligned} & \forall \chi \in [0, 1] : \mathbb{K}(\chi) \text{ is symmetric,} \\ & \exists K_1, K_2 > 0 \forall e \in \mathbb{R}^{d \times d} \forall \chi \in [0, 1] : |e|^2 K_1 \leq e : \mathbb{K}(\chi) : e \leq K_2 |e|^2. \end{aligned}$$

Recall that the positive definiteness of  $\mathbb{K}(\chi)$  for any  $\chi \in [0, 1]$  ensures some residual stiffness of the material even in the case of maximal damage  $\chi = 0$ .

**Assumptions on the inelastic strain  $\Xi$ :** For the inelastic strain  $\Xi : [0, 1] \times \mathbb{R}^{d \times d} \rightarrow \mathbb{R}^{d \times d}$  introduced in (1.2) we make the following assumptions:

$$(2.4a) \quad \Xi \in C^0([0, 1] \times \mathbf{S}; \mathbf{S}) \quad \text{s.t.}$$

$$(2.4b) \quad \forall \chi_1 < \chi_2 \in [0, 1], D \in \mathbf{S} : |\Xi(\chi_2, D)| \leq |\Xi(\chi_1, D)|. \quad \Xi(1, D) = 0 \text{ and } \Xi(0, D) = D.$$

For later use we remark that (2.4b) in particular implies that

$$(2.5) \quad |\Xi(\chi, D)| \leq |D| \quad \text{for all } (\chi, D) \in [0, 1] \times \mathbf{S}.$$

**Assumptions on the damage regularization:** In view of (1.11), given  $\mathbf{Z}$  from (2.2b), we define the damage regularization functional in terms of

$$(2.6a) \quad \mathcal{J} : \mathbf{Z} \rightarrow \mathbb{R}_\infty, \quad \mathcal{J}(\chi) := \int_{\Omega} J(\chi, \nabla \chi) \, dx \quad \text{with}$$

$$J(\chi, \nabla \chi) := I_{[0,1]}(\chi) + \tilde{J}(\chi, \nabla \chi)$$

and we assume that  $\tilde{J}$  has the following properties:

$$(2.6b) \quad \text{Continuity: } \tilde{J} \in C(\mathbb{R} \times \mathbb{R}^d; \mathbb{R}),$$

$$\text{Growth: } \exists c_J, \tilde{c}_J, C_J > 0, \exists r \in (1, \infty), \forall \chi \in [0, 1], A \in \mathbb{R}^d :$$

$$(2.6c) \quad c_J(|A|^r - \tilde{c}_J) \leq \tilde{J}(\chi, A) \leq C_J(|A|^r + 1),$$

$$(2.6d) \quad \text{Convexity: } \forall \chi \in [0, 1] : \tilde{J}(\chi, \cdot) \text{ is convex on } \mathbb{R}^{d \times d}.$$

Under these assumptions  $\mathcal{J}$  may e.g. be a pure (convex) gradient regularization (i.e.  $\tilde{J}$  does not depend on  $\chi$ ), but it may also incorporate terms like  $(1 - \chi)^2$  enforcing  $\chi$  to stay close to 1, hence inhibiting damage. Also nonconvex terms of lower order, e.g. double well potentials, may contribute to  $\tilde{J}$ , provided the leading term is convex. In particular, note that the density  $J$  considered in (1.13) is comprised in this set of assumptions.

**Assumptions on the plastic regularization:** In view of (1.11), given  $\mathbf{V}$  from (2.2e) and the subspace  $\mathbf{S} \subset \mathbb{R}^{d \times d}$ , we introduce the plastic regularization functional as follows

$$(2.7a) \quad \mathcal{G} : \mathbf{V} \rightarrow \mathbb{R}_\infty, \quad \mathcal{G}(D) := \begin{cases} \int_{\Omega} G(D, \nabla D) \, dx & \text{if } G(D, \nabla D) \in L^1(\Omega), \\ \infty & \text{otw.} \end{cases} \quad \text{with}$$

$$G(D, \nabla D) := I_K(D) + \tilde{G}(D, \nabla D),$$

where  $K$  is a closed, convex subset of  $\mathbf{S}$ , and we suppose that  $\tilde{G}$  has the following properties:

$$(2.7b) \quad \text{Continuity: } \tilde{G} \in C(\mathbb{R}^{d \times d} \times \mathbb{R}^{d^4}; \mathbb{R}),$$

$$\text{Growth: } \exists c_G, \tilde{c}_G, C_G > 0, \exists q, q_1 \text{ with } \tilde{q} := \frac{2d}{d+2} \leq q < q_1 \in [2, \infty), \forall D \in \mathbb{R}^{d \times d}, A \in \mathbb{R}^{d^4} :$$

$$(2.7c) \quad c_G(|A|^q + |D|^{q_1} - \tilde{c}_G) \leq \tilde{G}(D, A) \leq C_G(|A|^q + |D|^{q_1} + 1),$$

$$(2.7d) \quad \text{Convexity: } \forall D \in \mathbb{R}^{d \times d} : \tilde{G}(D, \cdot) \text{ is convex on } \mathbb{R}^{d^4}.$$

The assumption on the exponents  $q < q_1$  (which are the ones associated with the spaces  $\mathbf{H}$  and  $\mathbf{H}_1$ , cf. (2.2f) and (2.2g)), implies the coercivity of the integral functional  $\mathcal{G}$  wrt. the space  $W^{1,q}(\Omega; \mathbb{R}^{d \times d})$ . Moreover,  $q_1 \geq 2$  yields that  $D \in L^2(\Omega; \mathbb{R}^{d \times d})$  on energy sublevels, whereas the lower bound  $\frac{2d}{d+2} \leq q$  ensures that

$$(2.8) \quad W^{1,q}(\Omega; \mathbb{R}^{d \times d}) \Subset L^2(\Omega; \mathbb{R}^{d \times d}) \text{ compactly, with embedding constant } C_{\mathbf{H} \rightarrow L^2}.$$

Note that, for instance,  $G$  from (1.14) complies with the above growth assumptions if  $q \in [\tilde{q}, 4]$ .

**Assumptions on the coupling term:** In view of (1.11), (2.6a), and (2.7a) we introduce the coupling term as follows

$$(2.9a) \quad \mathcal{H} : \mathbf{Z} \times \mathbf{V} \rightarrow \mathbb{R} \quad \mathcal{H}(\chi, D) := \begin{cases} \int_{\Omega} H(\chi, D) \, dx & \text{if } (\chi, D) \in \mathbf{M} \times (\mathbf{H} \cap \mathbf{H}_1), \\ \infty & \text{if } (\chi, D) \in \mathbf{Z} \times \mathbf{V}, \end{cases}$$

and for the density  $H$  we assume

$$(2.9b) \quad \text{Continuity: } H \in C([0, 1] \times \mathbb{R}^{d \times d}; \mathbb{R}),$$

$$(2.9c) \quad \text{Growth: } \exists C_H > 0, \exists q_2 \in [1, q_*] \forall (\chi, D) \in [0, 1] \times \mathbb{R}^{d \times d}: 0 \leq H(\chi, D) \leq C_H(|D|^{q_2} + 1),$$

where  $q_* = dq/(d - q)$  if  $q < d$  and  $q_* = \infty$  if  $q \geq d$ . Note that  $q_2 \in [1, q_1]$  would be sufficient to ensure the integrability of  $H$ . But for the continuity of  $\mathcal{H}$  it is required that  $q_2 \in [1, q_*)$ . Also note that the special choice (1.12) of  $H$  complies with the above assumptions with  $q_2 \geq 2$ .

### 3. ENERGETIC SOLUTIONS FOR THE RATE-INDEPENDENT SYSTEM WITH DAMAGE AND PLASTICITY

In view of the positively 1-homogeneous character of the pseudo-potential of dissipation  $\mathcal{R}$  from (1.10), system (1.15) is rate-independent. Therefore, for the analysis of the associated initial-boundary value problem we will resort to a weak solvability concept for rate-independent systems, namely the notion of energetic solution, cf. [MT04, Mie05]. In order to give it in the context of the present system with damage and plasticity we now introduce the energy functional, depending on  $t \in [0, T]$  and on the state variables  $(\mathbf{u}, \chi, D)$ , and the dissipation potential associated with (1.15). In accordance with Sec. 2 we set

$$(3.1a) \quad \mathcal{R} = \mathcal{R}_{\text{inel}} + \mathcal{R}_{\text{dam}} : \mathbf{V} \times \mathbf{Z} \rightarrow \mathbb{R}_{\infty}, \quad \text{where,}$$

$$(3.1b) \quad \mathcal{R}_{\text{inel}} : \mathbf{V} \rightarrow [0, \infty), \quad \mathcal{R}_{\text{inel}}(A) := \int_{\Omega} R_{\text{inel}}(A) \, dx \quad \text{with } R_{\text{inel}}(A) := \mu|A|,$$

$$(3.1c) \quad \mathcal{R}_{\text{dam}} : \mathbf{Z} \rightarrow [0, \infty), \quad \mathcal{R}_{\text{dam}}(z) := \int_{\Omega} R_{\text{dam}}(z) \, dx \quad \text{with } R_{\text{dam}}(z) := \nu|z| + I_{(-\infty, 0]}(z),$$

$$(3.1d) \quad \mathcal{E} : [0, T] \times \mathbf{U} \times \mathbf{Z} \times \mathbf{V} \rightarrow \mathbb{R}_{\infty}, \quad \mathcal{E}(t, \mathbf{u}, \chi, D) := \mathcal{F}(\mathbf{u}, \chi, D) - \langle F(t), \mathbf{u} \rangle_{\mathbf{U}} \\ = \mathcal{W}(t, \mathbf{u}, \chi, D) + \mathcal{J}(\chi) + \mathcal{G}(D) + \mathcal{H}(\chi, D),$$

$$(3.1e) \quad \mathcal{W} : [0, T] \times \mathbf{U} \times \mathbf{M} \times L^2(\Omega; \mathbb{R}^{d \times d}) \rightarrow \mathbb{R},$$

$$\mathcal{W}(t, \mathbf{u}, \chi, D) := \frac{1}{2} \int_{\Omega} (e(\mathbf{u}) + e_D(t) - \Xi(\chi, D)) : \mathbb{K}(\chi) : (e(\mathbf{u}) + e_D(t) - \Xi(\chi, D)) \, dx \\ - \langle F(t), \mathbf{u} \rangle_{\mathbf{U}}.$$

In order to give the energetic concept we shall use the shorthand notation  $\mathbf{q} = (\mathbf{u}, \chi, D)$  and set  $\mathcal{Q} := \mathbf{U} \times \mathbf{Z} \times \mathbf{V}$ , the state space where  $\mathbf{q}$  varies, whereas  $\mathcal{Z} := \mathbf{Z} \times \mathbf{V}$  stands for the space of the *dissipative* variables  $z := (\chi, D)$ . In this way, we shall now state the definition of energetic solutions in an abstract form.

**Definition 3.1** (Energetic formulation of rate-independent processes). *For the initial datum  $\mathbf{q}_0 \in \mathcal{Q}$  find  $\mathbf{q} : [0, T] \rightarrow \mathcal{Q}$  such that for all  $t \in [0, T]$  the global stability (3.2a) and the global energy balance (3.2b) hold*

$$(3.2a) \quad \text{Stability:} \quad \text{for all } \tilde{\mathbf{q}} \in \mathcal{Q} : \quad \mathcal{E}(t, \mathbf{q}(t)) \leq \mathcal{E}(t, \tilde{\mathbf{q}}) + \mathcal{R}(\tilde{\mathbf{q}} - \mathbf{q}(t)),$$

$$(3.2b) \quad \text{Energy balance:} \quad \mathcal{E}(t, \mathbf{q}(t)) + \text{Diss}_{\mathcal{R}}(\mathbf{q}, [s, t]) = \mathcal{E}(0, \mathbf{q}(0)) + \int_s^t \partial_t \mathcal{E}(\xi, \mathbf{q}(\xi)) \, d\xi$$

with  $\text{Diss}_{\mathcal{R}}(\mathbf{q}, [0, t]) := \sup \left\{ \sum_{j=1}^N \mathcal{R}(\mathbf{q}(\xi_j) - \mathbf{q}(\xi_{j-1})) \mid s = \xi_0 < \dots < \xi_N = t, N \in \mathbb{N} \right\}$ , where  $\mathcal{R}(\mathbf{q}_1 - \mathbf{q}_2)$  has to be understood as  $\mathcal{R}(z_1 - z_2)$  with  $\mathbf{q}_i = (\mathbf{u}_i, z_i)$  for  $i = 1, 2$ .

The claim that (3.2) has to hold for all  $t \in [0, T]$  entails that the energetic formulation is only solvable for initial data  $\mathbf{q}_0$  which satisfy (3.2a) for  $t = 0$ . For later convenience we introduce

the set of stable states at time  $t \in [0, T]$

$$(3.3) \quad \mathcal{S}(t) := \{\mathbf{q} \in \mathcal{Q}, \mathbf{q} \text{ satisfies (3.2a) wrt. } \mathcal{E}(t, \cdot) \text{ and } \mathcal{R}\}.$$

A solution in terms of the energetic formulation is called an energetic solution to the rate-independent system  $(\mathcal{Q}, \mathcal{E}, \mathcal{R})$ .

In what follows we will investigate the existence of energetic solutions (3.2) for the rate-independent system with damage and plasticity defined by the functionals  $\mathcal{E}$  and  $\mathcal{R}$  from (3.1) by verifying the assumptions of an abstract existence theorem given in [Mie11b], cf. also [MT04, Mie05, MRS08]. We now shortly recap this result, highlighting the role of a series of conditions on the driving functionals  $\mathcal{E}$  and  $\mathcal{R}$  enucleated below, cf. (3.4)–(3.9).

This result is proved by passing to the limit in a time-discretization scheme, where discrete energetic solutions are constructed via time-incremental minimization of a functional involving the sum of the dissipation potential  $\mathcal{R}$  and the energy  $\mathcal{E}$ . The existence of minimizers follows from the *direct method*, provided that the energy functional  $\mathcal{E}$  complies with a standard coercivity requirement, cf. (3.4a) ahead. It is shown that the discrete solutions fulfill the stability condition and a discrete energy *inequality*. The proof of the discrete stability relies on the fact that the dissipation distance  $\mathcal{D}$  induced by  $\mathcal{R}$  complies with the triangle inequality, see (3.8a) later on. From the discrete energy inequality all a priori estimates are derived. For this, a crucial role is played by a condition ensuring that the power of the external forces  $\partial_t \mathcal{E}$  is controlled by the energy  $\mathcal{E}$  itself, cf. (3.4b) below, so that the last integral term on the right-hand side of (3.2b) is estimated in terms of the energy, and Gronwall's lemma can be applied. All in all,  $\mathcal{E}$  has to satisfy the following properties:

$$(3.4a) \quad \begin{aligned} & \text{Compactness of energy sublevels: } \forall t \in [0, T] \forall E \in \mathbb{R} : \\ & L_E(t) := \{\mathbf{q} \in \mathcal{Q} \mid \mathcal{E}(t, \mathbf{q}) \leq E\} \text{ is weakly seq. compact.} \end{aligned}$$

$$(3.4b) \quad \begin{aligned} & \text{Uniform control of the power:} \\ & \exists c_0 \in \mathbb{R} \exists c_1 > 0 \forall (t, \mathbf{q}) \in [0, T] \times \mathcal{Q} \text{ with } \mathcal{E}(t, \mathbf{q}) < \infty : \\ & \mathcal{E}(\cdot, \mathbf{q}) \in C^1([0, T]) \text{ and } |\partial_t \mathcal{E}(t, \mathbf{q})| \leq c_1(c_0 + \mathcal{E}(t, \mathbf{q})). \end{aligned}$$

**Remark 3.2.** Observe that condition (3.4b) in fact guarantees a Lipschitz estimate for  $\mathcal{E}$  with respect to time via Gronwall's lemma, namely

$$(3.5) \quad |\mathcal{E}(t, \mathbf{q}) - \mathcal{E}(s, \mathbf{q})| \leq \left( e^{c_1|t-s|} - 1 \right) (\mathcal{E}(t, \mathbf{q}) + c_0) \leq e^{c_1 T} (\mathcal{E}(t, \mathbf{q}) + c_0) |t - s|.$$

Hence, if  $\mathcal{E}(t, \mathbf{q}) < E$  for  $E \in \mathbb{R}$ , then, for  $c_E := e^{c_1 T}(E + c_0)$ , estimate (3.5) implies

$$(3.6) \quad |\mathcal{E}(t, \mathbf{q}) - \mathcal{E}(s, \mathbf{q})| \leq c_E |t - s|.$$

As for the dissipation potential  $\mathcal{R}$ , we require that the induced dissipation distance

$$(3.7) \quad \mathcal{D} : \mathcal{Z} \times \mathcal{Z} \rightarrow [0, \infty] \quad \text{given by} \quad \mathcal{D}(z, \tilde{z}) := \mathcal{R}(\tilde{z} - z) \quad \text{for all } z, \tilde{z} \in \mathcal{Z},$$

fulfills

$$(3.8a) \quad \begin{aligned} & \text{Quasi-distance: } \forall z_1, z_2, z_3 \in \mathcal{Z} : \quad \mathcal{D}(z_1, z_2) = 0 \Leftrightarrow z_1 = z_2 \quad \text{and} \\ & \mathcal{D}(z_1, z_3) \leq \mathcal{D}(z_1, z_2) + \mathcal{D}(z_2, z_3); \end{aligned}$$

$$(3.8b) \quad \begin{aligned} & \text{Semi-continuity:} \\ & \mathcal{D} : \mathcal{Z} \times \mathcal{Z} \rightarrow [0, \infty] \text{ is weakly sequentially lower semi-continuous.} \end{aligned}$$

The abstract existence proof then consists in passing to the limit in the discrete energy inequality by lower semicontinuity arguments, leading to an upper energy estimate, and in the discrete stability condition, leading to (3.2a). The lower energy estimate which ultimately yields the energy balance (3.2b) then follows from a by now classical procedure, based on the combination of the previously proved (3.2a) with a Riemann-sum argument. For the limit passage in the discrete energy inequality and in the discrete stability, the following compatibility conditions are required:

For every stable sequence  $(t_k, \mathbf{q}_k)_{k \in \mathbb{N}}$  with  $t_k \rightarrow t$ ,  $\mathbf{q}_k \rightharpoonup \mathbf{q}$  in  $[0, T] \times \mathcal{Q}$  we have

$$(3.9a) \quad \text{Convergence of the power of the energy: } \partial_t \mathcal{E}(t_k, \mathbf{q}_k) \rightarrow \partial_t \mathcal{E}(t, \mathbf{q}),$$

$$(3.9b) \quad \text{Closedness of sets of stable states: } \mathbf{q} \in \mathcal{S}(t).$$

With these prerequisites at hand the abstract existence result reads as follows:

**Theorem 3.3** (Abstract main existence theorem [Mie11b]). *Let the rate-independent system  $(\mathcal{Q}, \mathcal{E}, \mathcal{R})$  satisfy conditions (3.4) and (3.8). Moreover, let the compatibility conditions (3.9) hold. Then, for each  $\mathbf{q}_0 \in \mathcal{S}(0)$  there exists an energetic solution  $\mathbf{q} : [0, T] \rightarrow \mathcal{Q}$  for  $(\mathcal{Q}, \mathcal{E}, \mathcal{R})$  satisfying  $\mathbf{q}(0) = \mathbf{q}_0$ .*

From Thm. 3.3 we will derive our own existence result for the rate-independent system with damage and plasticity.

**Theorem 3.4** (Existence of energetic solutions for the rate-independent system from (3.1)). *Let the assumptions (2.1) and (2.3)–(2.9) stated in Sec. 2 be satisfied. Then the rate-independent system for damage and plasticity  $(\mathcal{Q}, \mathcal{E}, \mathcal{R})$  given by (3.1) satisfies the properties (3.4), (3.8) & (3.9), and hence, for each  $\mathbf{q}_0 \in \mathcal{Q}$  with  $\mathbf{q}_0 \in \mathcal{S}(0)$  it admits an energetic solution in the sense of Def. 3.1.*

#### 4. PROOF OF THEOREM 3.4

It is immediate to observe that the dissipation distance generated by the potential  $\mathcal{R}$  from (3.1c) via formula (3.7) satisfies the abstract condition (3.8). Thus, it remains to verify that the energy functional  $\mathcal{E}$  from (3.1d) satisfies the basic properties (3.4). In addition, the compatibility conditions (3.9) have to be deduced.

To this aim, we start with verifying the following regularity property for the inelastic strain.

**Lemma 4.1.** *Let (2.4) and (2.8) hold true, let  $\alpha \in [1, \infty)$ . Then,  $\Xi : \mathbf{M} \times L^2(\Omega; \mathbf{S}) \rightarrow L^2(\Omega; \mathbf{S})$  is continuous wrt. the  $L^\alpha(\Omega) \times L^2(\Omega; \mathbf{S})$ -topology.*

PROOF. Consider  $(\chi_k, D_k)_k \subset \mathbf{M} \times L^2(\Omega; \mathbf{S})$  such that  $(\chi_k, D_k)_k \rightarrow (\chi, D)$  in  $L^\alpha(\Omega) \times L^2(\Omega; \mathbf{S})$ . Hence, up to a subsequence we find that  $(\chi_k, D_k)_k \rightarrow (\chi, D)$  pointwise a.e. in  $\Omega$ . Thanks to (2.4a) we find that  $|\Xi(\chi_k, D_k)|^2 \rightarrow |\Xi(\chi, D)|^2$  pointwise a.e. in  $\Omega$ . Moreover, (2.4b) ensures  $|\Xi(\chi_k, D_k)|^2 \leq |\Xi(0, D_k)|^2 = |D_k|^2$  for all  $k \in \mathbb{N}$ , which thus serves as a convergent majorant. Hence,  $\Xi(\chi_k, D_k) \rightarrow \Xi(\chi, D)$  in  $L^2(\Omega; \mathbb{R}^{d \times d})$  by the dominated convergence theorem.  $\blacksquare$

The above continuity property is an important ingredient for the verification of the following properties of the functional  $\mathcal{W}$  :

**Lemma 4.2** (Properties of  $\mathcal{W}$ ). *The functional  $\mathcal{W} : [0, T] \times \mathbf{U} \times \mathbf{M} \times L^2(\Omega; \mathbf{S}) \rightarrow \mathbb{R}$  from (3.1e) has the following properties:*

$$(4.1) \quad \begin{aligned} \text{bound from below: } & \exists c_W, \tilde{c}_W, C_W > 0, \forall (t, \mathbf{u}, \chi, D) \in [0, T] \times \mathbf{U} \times (\mathbf{X} \cap \mathbf{M}) \times \mathbf{H} : \\ & \mathcal{W}(t, \mathbf{u}, \chi, D) \geq c_W \|\mathbf{u}\|_{\mathbf{U}}^2 - \tilde{c}_W \|D\|_{L^2(\Omega; \mathbb{R}^{d \times d})}^2 - C_W, \end{aligned}$$

$$(4.2) \quad \begin{aligned} \text{lower semicontinuity: } & \mathcal{W} \text{ is lower semicontinuous wrt. the weak convergence in } \mathbf{U} \\ & \text{and strong convergence in } L^\alpha(\Omega) \times L^2(\Omega; \mathbf{S}) \text{ for all } \alpha \in [1, \infty). \end{aligned}$$

Moreover, for all  $(t, \mathbf{u}, \chi, D) \in [0, T] \times \mathbf{U} \times \mathbf{X} \cap \mathbf{M} \times (\mathbf{H} \cap \mathbf{H}_1)$  the partial time-derivative  $\partial_t \mathcal{W}$  is given by

$$(4.3) \quad \partial_t \mathcal{W}(t, \mathbf{u}, \chi, D) := \int_{\Omega} (e(\mathbf{u}) + e_D(t) - \Xi(\chi, D)) : \mathbb{K}(\chi) : \partial_t e_D(t) \, dx - \langle F_t(t), \mathbf{u} \rangle_{\mathbf{U}}$$

and  $\mathcal{W} + \mathcal{G}$  satisfies relation (3.4b).

PROOF. We split the proof in several steps.

**Ad bound from below (4.1):** Thanks to the positive definiteness of  $\mathbb{K}$ , the bounds on the we given data  $F, g$ , cf. (2.3), and the properties of  $\Xi$  from (2.4), also using Young's and Korn's

inequality as well as estimate (2.5), we find for all  $(t, \mathbf{u}, \chi, D) \in [0, T] \times \mathbf{U} \times (\mathbf{X} \cap \mathbf{M}) \times (\mathbf{H} \cap \mathbf{H}_1)$

$$\begin{aligned}
\mathcal{W}(t, \mathbf{u}, \chi, D) &\geq \|e(\mathbf{u}) + e_D - \Xi(\chi, D)\|_{L^2(\Omega; \mathbb{R}^{d \times d})}^2 - C_F \|\mathbf{u}\|_{\mathbf{U}} \\
&\geq (\|e(\mathbf{u})\|_{L^2} - (C_D + \|\Xi(\chi, D)\|_{L^2}))^2 - C_F \|\mathbf{u}\|_{\mathbf{U}} \\
&\stackrel{(2.5)}{\geq} \frac{1}{2} \|e(\mathbf{u})\|_{L^2}^2 - 8(C_D + \|D\|_{L^2})^2 - C_F \|\mathbf{u}\|_{\mathbf{U}} \\
&\geq \frac{C_K^2}{2} \|\mathbf{u}\|_{\mathbf{U}}^2 - 16(C_D^2 + \|D\|_{L^2}^2) - \frac{C_K^2}{4} \|\mathbf{u}\|_{\mathbf{U}}^2 - \frac{4}{C_K^2} C_F^2,
\end{aligned}$$

using the short-hand  $\|\cdot\|_{L^2}$  for  $\|\cdot\|_{L^2(\Omega; \mathbb{R}^{d \times d})}$ , and with  $C_K$  the constant in Korn's inequality. This proves (4.1).

**Ad lower semicontinuity (4.2):** For every  $t \in [0, T]$  we observe that  $\mathcal{W}(t, \cdot, \cdot, \cdot)$  is continuous wrt. the strong convergence in  $L^2(\Omega; \mathbb{R}^{d \times d}) \times L^\alpha(\Omega) \times L^2(\Omega; \mathbf{S})$ , also due to estimate (2.5). Moreover, for every  $(t, \chi, D)$  in  $[0, T] \times (L^\alpha(\Omega) \cap \mathbf{M}) \times L^2(\Omega; \mathbf{S})$  the functional  $\mathcal{W}(t, \cdot, \chi, D) : \mathbf{U} \rightarrow \mathbb{R}$  is convex and we have  $\mathcal{W}(t, \mathbf{u}, \chi, D) \geq -K_1 \int_\Omega |D| |e(\mathbf{u}) + e_D(t)| dx - \langle F(t), \mathbf{u}(t) \rangle_{\mathbf{U}}$ . Hence, [FL07, p. 492, Thm. 7.5] guarantees the lower semicontinuity statement (4.2).

**Ad (4.3) & relation (3.4b):** Formula (4.3) ensues from a direct calculation, taking into account that  $\mathcal{W}(t, \cdot, \chi, D)$  is Fréchet-differentiable in  $L^2(\Omega; \mathbb{R}^d)$ , as well as the regularity properties of  $F$  and  $\mathbf{u}_D$ , cf. (2.3). Note now that  $\partial_t(\mathcal{W} + \mathcal{G}) = \partial_t \mathcal{W}$ . In order to find the bound (3.4b) on  $|\partial_t \mathcal{W}(t, \mathbf{u}, \chi, D)|$  we make use of the growth properties of  $\mathbb{K}$ , cf. (2.3), Hölder's and Young's inequality, and exploit the already deduced bound (4.1). This yields

$$\begin{aligned}
|\partial_t \mathcal{W}(t, \mathbf{u}, \chi, D)| &\leq K_2 C_D (\|e(\mathbf{u})\|_{L^2}^2 + \|e_D\|_{L^2}^2 + \|\Xi(\chi, D)\|_{L^2}^2 + 2) + \frac{1}{2} (C_F^2 + \|\mathbf{u}\|_{\mathbf{U}}^2) \\
&\leq C \|\mathbf{u}\|_{\mathbf{U}}^2 + c \|D\|_{L^2}^2 + C_3 \\
&\leq \tilde{C} \mathcal{W}(t, \mathbf{u}, \chi, D) + \tilde{c} \|D\|_{L^{q_1}}^{q_1} + C_4 \\
&\leq C_5 (\mathcal{W}(t, \mathbf{u}, \chi, D) + \mathcal{G}(D)) + C_6,
\end{aligned}$$

where the last estimate follows from the coercivity properties of  $\mathcal{G}$ , cf. (4.7b). This finishes the proof of (3.4b).  $\blacksquare$

**Lemma 4.3** (Weak lower semicontinuity). *Let  $\mathbf{B}_1 \subset \mathbf{B}_2$  with a continuous embedding be separable Banach spaces and  $\mathbf{B}_1$  reflexive. Assume that the functional  $\mathcal{E}_1 : \mathbf{B}_1 \rightarrow \mathbb{R}$  is weakly sequentially lower semicontinuous and coercive. Then the extended functional  $\mathcal{E}_2 : \mathbf{B}_2 \rightarrow \mathbb{R}$  is also weakly sequentially lower semicontinuous, where*

$$(4.4) \quad \mathcal{E}_2(v) := \begin{cases} \mathcal{E}_1(v) & \text{if } v \in \mathbf{B}_1, \\ \infty & \text{if } v \in \mathbf{B}_2 \setminus \mathbf{B}_1. \end{cases}$$

**PROOF.** Consider a sequence  $v_k \rightharpoonup v$  in  $\mathbf{B}_2$ . If  $v_k \in \mathbf{B}_2 \setminus \mathbf{B}_1$  for  $k \in \mathbb{N}$  except of a finite number of indices, then  $\mathcal{E}_2(v) \leq \liminf_{k \rightarrow \infty} \mathcal{E}_2(v_k) = \infty$ . Also, if  $\|v_k\|_{\mathbf{B}_1} \rightarrow \infty$  for any subsequence, then  $\mathcal{E}_2(v) \leq \liminf_{k \rightarrow \infty} \mathcal{E}_2(v_k) = \infty$ . Hence, in these two cases there is nothing to prove. Thus, assume that  $\|v_k\|_{\mathbf{B}_1} \leq C$  for a not relabelled subsequence  $(v_k)_k$  and a constant  $C > 0$ . From the reflexivity of  $\mathbf{B}_1$  we now conclude that there is a further, not relabelled subsequence and an element  $\tilde{v} \in \mathbf{B}_1$  such that  $v_k \rightharpoonup \tilde{v}$  in  $\mathbf{B}_1$ . By the uniqueness of the limit in  $\mathbf{B}_2 \supset \mathbf{B}_1$  we have that  $\tilde{v} = v$ . Now the weak lower semicontinuity of  $\mathcal{E}_1 : \mathbf{B}_1 \rightarrow \mathbb{R}$  implies that  $\mathcal{E}_2(v) = \mathcal{E}_1(v) \leq \liminf_{k \rightarrow \infty} \mathcal{E}_1(v_k) \leq \liminf_{k \rightarrow \infty} \mathcal{E}_2(v_k)$ , which proves the assertion.  $\blacksquare$

**Lemma 4.4** (Properties of  $\mathcal{H}$ ,  $\mathcal{J}$ , and  $\mathcal{G}$ ). *Let the coupling term  $\mathcal{H}$  be defined as in (2.9) and let  $\alpha \in [1, \infty)$ . Then  $\mathcal{H}$  has the following properties:*

- (4.5a) *proper domain:*  $\text{dom } \mathcal{H} = \mathbf{M} \times \mathbf{V}$ ,
- (4.5b) *bound from below:*  $\forall (\chi, D) \in \mathbf{Z} \times \mathbf{V} : \mathcal{H}(\chi, D) \geq 0$ ,
- (4.5c) *lower semicontinuity:*  $\mathcal{H} : \mathbf{Z} \times \mathbf{V} \rightarrow [0, \infty]$  is lower semicontinuous wrt. the strong convergence in  $L^\alpha(\Omega) \times L^{q_2}(\Omega, \mathbb{R}^{d \times d})$  for every  $\alpha \in [1, \infty)$ .

Let the damage regularization  $\mathcal{J}$  be given by (2.6a). Then, the following properties hold true:

- (4.6a) *proper domain:*  $\text{dom } \mathcal{J} = (\mathbf{X} \cap \mathbf{M})$ ,  
(4.6b) *bound from below:*  $\exists c_{\mathcal{J}}, C_{\mathcal{J}} > 0, \forall \chi \in (\mathbf{X} \cap \mathbf{M}) : \mathcal{J}(\chi) \geq c_{\mathcal{J}} \|\chi\|_{\mathbf{X}}^2 - C_{\mathcal{J}}$ ,  
(4.6c) *lower semicontinuity:*  $\mathcal{J}$  is lower semicontinuous wrt. the weak convergence in  $\mathbf{X}$ .

Let the plastic regularization  $\mathcal{G}$  be given as in (2.7a). Then, the following properties are satisfied:

- (4.7a) *proper domain:*  $\text{dom } \mathcal{G} \subset (\mathbf{H} \cap \mathbf{H}_1)$  is a closed, convex subset,  
(4.7b) *bound from below:*  $\exists c_{\mathcal{G}}, C_{\mathcal{G}} > 0, \forall D \in \text{dom } \mathcal{G} : \mathcal{G}(D) \geq c_{\mathcal{G}} \|D\|_{\mathbf{H}}^q - C_{\mathcal{G}}$ ,  
 $\mathcal{G}(D) \geq c_{\mathcal{G}} \|D\|_{\mathbf{H}_1}^{q_1} - C_{\mathcal{G}}$ ,  
(4.7c) *lower semicontinuity:*  $\mathcal{G}$  is lower semicontinuous wrt. weak convergence in  $(\mathbf{H} \cap \mathbf{H}_1)$ .

Hence, the functionals  $\mathcal{J} : \mathbf{Z} \rightarrow \mathbb{R}_{\infty}$  and  $\mathcal{G} : \mathbf{V} \rightarrow \mathbb{R}_{\infty}$  are weakly sequentially lower semicontinuous.

PROOF. We split the proof in several steps.

**Ad (4.5):** The domain property (4.5a) and the boundedness from below are a direct consequence of definition (2.9a) and (2.9c). The lower semicontinuity can be concluded from the continuity (2.9b) and the growth property (2.9c) as follows. Given a sequence  $(\chi_k, D_k)_k \subset (\mathbf{Z} \setminus \mathbf{M}) \times \mathbf{V}$ , with  $(\chi_k, D_k) \rightarrow (\chi, D)$  in  $L^\alpha(\Omega) \times L^{q_2}(\Omega, \mathbb{R}^{d \times d})$ , we immediately find that  $\infty = \liminf_{k \rightarrow \infty} \mathcal{H}(\chi_k, D_k) \geq \mathcal{H}(\chi, D)$ , while no matter occurs if  $(\chi, D) \in \mathbf{M} \times \mathbf{V}$ . Hence assume that there is a (not relabelled) subsequence  $(\chi_k, D_k)_k \subset \mathbf{M} \times \mathbf{V}$  such that  $(\chi_k, D_k) \rightarrow (\chi, D)$  in  $L^\alpha(\Omega) \times L^{q_2}(\Omega, \mathbb{R}^{d \times d})$ . Upon extraction of a further subsequence that converges pointwise a.e. in  $\Omega$  we find that the limit  $(\chi, D) \in \mathbf{M} \times \mathbf{V}$ . Moreover, thanks to the continuity (2.9b) we have that  $H(\chi_k, D_k) \rightarrow H(\chi, D)$  a.e. in  $\Omega$  along this subsequence. In addition, for each  $k \in \mathbb{N}$ , the growth property (2.9c) guarantees the convergent majorant  $C_H(|D|^{q_2} + 1) \geq H(\chi_k, D_k)$ , so that the convergence of the respective integral terms is implied by the dominated convergence theorem. Thus, altogether, we have verified the lower semicontinuity property stated in (4.5c).

**Ad (4.6) & (4.7):** Properties (4.6a) and (4.7a) are implied by (2.6a) and (2.7a), respectively. The bounds (4.6b) and (4.7b) immediately follow from the growth properties (2.6c) and (2.7c). Invoking [FL07, p. 492, Thm. 7.5], the latter, together with the continuity (2.6b), resp. (2.7b) and the convexity property (2.6d), resp. (2.7d), also ensure the weak sequential lower semicontinuity.

The last statement of the lemma follows from (4.6c) and (4.7c) as a direct consequence of Lemma 4.3.  $\blacksquare$

We are now in the position to conclude properties (3.4) for  $\mathcal{E}$  in consequence of Lemmata 4.1–4.4.

**Corollary 4.5** (Properties (3.4) of  $\mathcal{E}$ ). *Let the functional  $\mathcal{E} : [0, T] \times \mathbf{U} \times \mathbf{Z} \times \mathbf{V} \rightarrow \mathbb{R}_{\infty}$  be defined as in (3.1d). Let the assumptions of Lemmata 4.1–4.4 hold true. Then, the functional  $\mathcal{E}$  satisfies properties (3.4).*

PROOF. We split the proof in several steps.

**Ad compactness of the sublevels (3.4a):** Comparing (4.1) with (4.7b), using Hölder's and Young's inequality, we first deduce for  $D$ :

$$\begin{aligned} -\bar{c}_W \|D\|_{L^2(\Omega, \mathbb{R}^{d \times d})}^2 &\geq -\|D\|_{\mathbf{H}_1}^2 \bar{c}_W \mathcal{L}^d(\Omega)^{(q_1-2)/q_1} \\ &\geq -\frac{2c_{\mathcal{G}}}{q_1} \|D\|_{\mathbf{H}_1}^{q_1} - \frac{q_1-2}{q_1} (c_{\mathcal{G}}^{-2/q_1} \bar{c}_W \mathcal{L}^d(\Omega)^{(q_1-2)/q_1})^{(q_1-2)/q_1}, \end{aligned}$$

where  $2/q_1 < 1$  according to (2.7c). Thus, combining bounds (4.1), (4.5b), (4.6b), and (4.7b) yields that  $\mathcal{E}$  has sublevels bounded in  $\mathbf{U} \times \mathbf{X} \times (\mathbf{H} \cap \mathbf{H}_1)$ . Since this space is reflexive, the sublevels are then sequentially weakly compact, and so they are in  $\mathcal{Q} = \mathbf{U} \times \mathbf{Z} \times \mathbf{V}$ .

**Ad uniform control of the power (3.4b):** Since  $\partial_t \mathcal{E}(t, \mathbf{u}, \chi, D) = \partial_t \mathcal{W}(t, \mathbf{u}, \chi, D)$ , given by (4.3), the last statement of Lemma 4.2 ensures (3.4b) for  $\mathcal{E}$  upon adding  $\mathcal{H}(\chi, D) > 0$  and  $\mathcal{J}(\chi) + C_{\mathcal{J}} > 0$ .  $\blacksquare$

Finally, we verify that the rate-independent system  $(\mathcal{Q}, \mathcal{E}, \mathcal{R})$  for plasticity and damage satisfies the compatibility conditions (3.9).

**Proposition 4.6** (Compatibility conditions (3.9)). *Let the assumptions of Theorem 3.4 hold true. Then the rate-independent system  $(\mathcal{Q}, \mathcal{E}, \mathcal{R})$  for plasticity and damage satisfies the compatibility conditions (3.9).*

PROOF. In view of (3.6) we infer for any stable sequences  $(t_k, \mathbf{u}_k, \chi_k, D_k)_k \subset \mathcal{S}(t)$  that there is a constant  $E > 0$  such that this sequence belongs to same the energy sublevel  $L_E(t)$ , which is bounded in  $\mathbf{U} \times \mathbf{X} \times (\mathbf{H} \cap \mathbf{H}_1)$  as guaranteed by Cor. 4.5. Hence, we deduce the following convergence properties along a (not relabelled) subsequence:

$$\begin{aligned} (4.8a) \quad & \mathbf{u}_k \rightharpoonup \mathbf{u} \quad \text{in } \mathbf{U}, \\ (4.8b) \quad & D_k \rightharpoonup D \quad \text{in } \mathbf{H}, \\ (4.8c) \quad & D_k \rightarrow D \quad \text{in } L^{q_1}(\Omega, \mathbb{R}^{d \times d}) \cap L^{q_2}(\Omega, \mathbb{R}^{d \times d}), \\ (4.8d) \quad & \chi_k \rightharpoonup \chi \quad \text{in } \mathbf{X}, \\ (4.8e) \quad & \chi_k \rightarrow \chi \quad \text{in } L^\alpha(\Omega) \text{ for any } \alpha \in [1, \infty). \end{aligned}$$

**Ad (3.9a) convergence of the power  $\partial_t \mathcal{E}(t_k, q_k)$ :** In view of the above convergences, property (3.9a) can be concluded from weak-strong convergence arguments using that  $e_D(t_k) \rightarrow e_D(t)$  strongly in  $\mathbf{U}$  and  $F(t_k) \rightarrow F(t)$  strongly in  $\mathbf{U}^*$  thanks to the regularity assumptions (2.3).

**Ad closedness of sets of stable states (3.9b):** In order to deduce (3.9b), we make use of the so-called mutual recovery condition, i.e. *for every sequence  $(\mathbf{u}_k, \chi_k, D_k)_k \subset \mathcal{S}(t)$  converging to a limit  $(\mathbf{u}, \chi, D)$  in the sense of (4.8), and any competitor  $(\hat{\mathbf{u}}, \hat{\chi}, \hat{D})$ , it must be possible to construct a mutual recovery sequence  $(\hat{\mathbf{u}}_k, \hat{\chi}_k, \hat{D}_k)_k$  such that*

$$(4.9) \quad \limsup_{k \rightarrow \infty} (\mathcal{E}(t, \hat{q}_k) - \mathcal{E}(t, q_k) + \mathcal{R}(\hat{q}_k - q_k)) \leq \mathcal{E}(t, \hat{q}) - \mathcal{E}(t, q) + \mathcal{R}(\hat{q} - q),$$

where we again abbreviated  $\hat{q}_k = (\hat{\mathbf{u}}_k, \hat{\chi}_k, \hat{D}_k)$ , etc..

Let  $\hat{q} = (\hat{\mathbf{u}}, \hat{\chi}, \hat{D})$  such that  $\mathcal{E}(t, \hat{q}) < \infty$ . Then, a suitable recovery sequence is defined by

$$\begin{aligned} (4.10a) \quad & \hat{\mathbf{u}}_k := \hat{\mathbf{u}}, \\ (4.10b) \quad & \hat{\chi}_k := \min\{\chi_k, \max\{0, \hat{\chi} - \delta_k\}\}, \\ (4.10c) \quad & \hat{D}_k := \hat{D}, \end{aligned}$$

where  $\delta_k$  in (4.10b) is suitably chosen in dependence of  $\|\chi_k - \chi\|_{\mathbf{X}}$  such that  $\delta_k \rightarrow 0$  as  $k \rightarrow \infty$ , see [TM10] for the details. We refer to [LRTR14, Thm. 4.5] for the proof of the following convergence property:

$$(4.11) \quad \hat{\chi}_k \rightharpoonup \hat{\chi} \text{ in } \mathbf{X} \text{ as well as } \limsup_{k \rightarrow \infty} (\mathcal{J}(\hat{\chi}_k) - \mathcal{J}(\chi_k)) \leq \mathcal{J}(\hat{\chi}) - \mathcal{J}(\chi).$$

The convergence stated in (4.11) together with (4.10c) yields that  $\mathcal{R}(\hat{\chi}_k - \chi_k, \hat{D}_k - D_k) \rightarrow \mathcal{R}(\hat{\chi} - \chi, \hat{D} - D)$ . Moreover, upon choosing a further subsequence  $(\hat{\mathbf{u}}_k, \hat{\chi}_k, \hat{D}_k)_k$ , which converges pointwise a.e. in  $\Omega$ , and by making use of the bounds (2.3), we may conclude via the dominated convergence theorem, also taking into account the growth properties (2.9c) of  $\mathcal{H}$ , that

$$\mathcal{W}(t, \hat{\mathbf{u}}_k, \hat{\chi}_k, \hat{D}_k) \rightarrow \mathcal{W}(t, \hat{\mathbf{u}}, \hat{\chi}, \hat{D}) \text{ and } \mathcal{H}(\hat{\chi}_k, \hat{D}_k) \rightarrow \mathcal{H}(\hat{\chi}, \hat{D}),$$

whereas we clearly have  $\mathcal{G}(\hat{D}_k) \rightarrow \mathcal{G}(\hat{D})$ . The respective expressions for  $(\mathbf{u}_k, \chi_k, D_k)$  can be handled by weak lower semicontinuity. Ultimately, we conclude (4.9), which finishes the proof.  $\blacksquare$

## REFERENCES

- [AKS10] Fiaschi A., D. Knees, and U. Stefanelli. Young-measure quasi-static damage evolution. *J. Math. Anal. Appl.*, 401:269–288, 2010.
- [AMV14] R. Alessi, J.J. Marigo, and S. Vidoli. Gradient damage models coupled with plasticity and nucleation of cohesive cracks. *Archive for Rational Mechanics and Analysis*, 214(2):575–615, 2014.
- [BMR09] G. Bouchitté, A. Mielke, and T. Roubíček. A complete-damage problem at small strain. *Zeit. angew. Math. Phys.*, 60:205–236, 2009.
- [BMR12] S. Bartels, A. Mielke, and T. Roubíček. Quasistatic small-strain plasticity in the limit of vanishing hardening and its numerical approximation. *SIAM J. Numer. Anal.*, 50(2):951–976, 2012.
- [BR08] S. Bartels and T. Roubíček. Thermoviscoplasticity at small strains. *ZAMM Z. Angew. Math. Mech.*, 2008.

- [BS04] E. Bonetti and G. Schimperna. Local existence for Frémond’s model of damage in elastic materials. *Contin. Mech. Thermodyn.*, 16(4):319–335, 2004.
- [BSS05] E. Bonetti, G. Schimperna, and A. Segatti. On a doubly nonlinear model for the evolution of damaging in viscoelastic materials. *J. Differential Equations*, 218(1):91–116, 2005.
- [CL15] V. Crismale and G. Lazzaroni. Viscous approximation of quasistatic evolutions for a coupled elastoplastic-damage model. *Preprint SISSA 05/2015/MATE*, 2015.
- [Cri] V. Crismale. Globally stable quasistatic evolution for a coupled elastoplastic-damage model. *ESAIM Control Optim. Calc. Var.* to appear.
- [DMDM06] G. Dal Maso, A. DeSimone, and M.G. Mora. Quasistatic evolution problems for linearly elastic-perfectly plastic materials. *Arch. Rational Mech. Anal.*, 180:237–291, 2006.
- [DMDMM08] G. Dal Maso, A. DeSimone, M.G. Mora, and M. Morini. Globally stable quasistatic evolution in plasticity with softening. *Netw. Heterog. Media*, 3:567–614, 2008.
- [DMI13] G. Dal Maso and F. Iurlano. Fracture models as Gamma-limits of damage models. *Commun. Pure Appl. Anal.*, pages 1657–1686, 2013.
- [DMS14] G. Dal Maso and R. Scala. Quasistatic evolution in perfect plasticity as limit of dynamic processes. *J. Dynam. Differential Equations*, 26:915–954, 2014.
- [DPO93] Gianpietro Del Piero and David R. Owen. Structured deformations of continua. *Arch. Rational Mech. Anal.*, 124(2):99–155, 1993.
- [FG06] G. Francfort and A. Garroni. A variational view of partial brittle damage evolution. *Arch. Rational Mech. Anal.*, 182:125–152, 2006.
- [FL07] I. Fonseca and G. Leoni. *Modern Methods in the Calculus of Variations:  $L^p$  Spaces*. Springer, 2007.
- [FN96] M. Frémond and B. Nedjar. Damage, gradient of damage and principle of virtual power. *Internat. J. Solids Structures*, 33:1083–1103, 1996.
- [FRC10] Francesco Freddi and Gianni Royer-Carfagni. Regularized variational theories of fracture: a unified approach. *J. Mech. Phys. Solids*, 58(8):1154–1174, 2010.
- [Fré02] M. Frémond. *Non-Smooth Thermomechanics*. Springer-Verlag Berlin Heidelberg, 2002.
- [Gia05] A. Giacomini. Ambrosio-Tortorelli approximation of quasi-static evolution of brittle fracture. *Calc. Var. Partial Differential Equations*, 22:129–172, 2005.
- [GL09] A. Garroni and C. Larsen. Threshold-based quasi-static brittle damage evolution. *Arch. Ration. Mech. Anal.*, 194(2):585–609, 2009.
- [Hil50] R. Hill. *The mathematical theory of plasticity*. Oxford University Press, Oxford-New York, 1950.
- [HK15] C. Heinemann and C. Kraus. Complete damage in linear elastic materials – modeling, weak formulation and existence results. *Calc. Var. Partial Differ. Equ.*, 54:217–250, 2015.
- [HR99] W. Han and B.D. Reddy. *Plasticity (Mathematical Theory and Numerical Analysis)*, volume 9 of *Interdisciplinary Applied Mathematics*. Springer-Verlag, New York, 1999.
- [JRZ13] M. Jirásek, Rokoš, and J. Zeman. Localization analysis of variationally based gradient plasticity model. *Int. J. Solids and Structures*, (1):256–269, 2013.
- [JZ15] Jirásek and J. Zeman. Localization study of a regularized variational damage model. *Int. J. Solids and Structures*, 69–70:131–15, 2015.
- [Kac90] L.M. Kachanov. *Introduction to Continuum Damage Mechanics*. Mechanics of Elastic Stability. Kluwer Academic Publishers, second edition edition, 1990.
- [Kne09] D. Knees. Short note on global spatial regularity in elasto-plasticity with linear hardening. *Calc. Var. Partial Differ. Equ.*, 2009.
- [Kne10] D. Knees. On global spatial regularity and convergence rates for time-dependent elasto-plasticity. *Math. Models Methods Appl. Sci.*, 20(10):1823–1858, 2010.
- [KRZ13] D. Knees, R. Rossi, and C. Zanini. A vanishing viscosity approach to a rate-independent damage model. *Math. Models Methods Appl. Sci.*, 23:565–616, 2013.
- [LRTR14] G. Lazzaroni, R. Rossi, M. Thomas, and Toader R. Rate-independent damage in thermo-viscoelastic materials with inertia. *wias-preprint 2025*. 2014.
- [Lub90] J. Lubliner. *Plasticity theory*. Macmillan, New York, 1990.
- [Mie05] A. Mielke. Evolution in rate-independent systems (Ch.6). In C.M. Dafermos and E. Feireisl, editors, *Handbook of Differential Equations, Evolutionary Equations, vol. 2*, pages 461–559. Elsevier B.V., Amsterdam, 2005.
- [Mie11a] A. Mielke. Complete-damage evolution based on energies and stresses. *Discrete Contin. Dyn. Syst. Ser. S*, 4:423–439, 2011.
- [Mie11b] A. Mielke. *Differential, energetic and metric formulations for rate-independent processes*. In: *Non-linear PDE’s and applications*, volume 2028 of *Lecture Notes in Mathematics*. Springer, Heidelberg; Fondazione C.I.M.E., Florence, 2011. Notes of the C.I.M.E. Summer School held in Cetraro, June 23–28, 2008, Edited by Luigi Ambrosio and Giuseppe Savaré, Centro Internazionale Matematico Estivo (C.I.M.E.) Summer Schools.
- [MM05] A. Mainik and A. Mielke. Existence results for energetic models for rate-independent systems. *Calc. Var. PDEs*, 22:73–99, 2005.
- [MR06] A. Mielke and T. Roubíček. Rate-independent damage processes in nonlinear elasticity. *M<sup>3</sup>AS Math. Models Methods Appl. Sci.*, 16:177–209, 2006.

- [MRS08] A. Mielke, T. Roubíček, and U. Stefanelli.  $\Gamma$ -limits and relaxations for rate-independent evolutionary problems. *Calc. Var. Partial Differ. Equ.*, 31:387–416, 2008.
- [MRZ10] A. Mielke, T. Roubíček, and Zeman. Complete damage in elastic and viscoelastic media and its energetics. *Computer Methods in Applied Mechanics and Engineering*, (21-22):1242–1253, 2010.
- [MT04] A. Mielke and F. Theil. On rate-independent hysteresis models. *Nonl. Diff. Eqns. Appl. (NoDEA)*, 11:151–189, 2004.
- [PM13] K. Pham and J.J. Marigo. From the onset of damage to rupture: Construction of responses with damage localization for a general class of gradient damage models. *Continuum Mechanics and Thermodynamics*, 25:147–171, 2013.
- [RDG08] F. Ragueneau, R. Desmorat, and F. Gatuingt. Anisotropic damage modelling of biaxial behaviour and rupture of concrete structures. *Computers and concrete*, 5(4):417–434, 2008.
- [Tem85] R. Temam. *Mathematical Problems in plasticity*. Gauthier-Villars, 1985.
- [Tho13] M. Thomas. Quasistatic damage evolution with spatial BV-regularization. *DCDS-S*, 6(1):235–255, 2013.
- [TM10] M. Thomas and A. Mielke. Damage of nonlinearly elastic materials at small strain: existence and regularity results. *Zeit. angew. Math. Mech.*, 90(2):88–112, 2010.

DIPARTIMENTO DI MATEMATICA, UNIVERSITÀ DEGLI STUDI DI PAVIA, VIA FERRATA 1, I-27100, PAVIA, ITALY. E-MAIL: ELENA.BONETTI@UNIPV.IT

WEIERSTRASS INSTITUTE FOR APPLIED ANALYSIS AND STOCHASTICS, MOHRENSTR. 39, D-10117 BERLIN, GERMANY AND DIPARTIMENTO DI MATEMATICA, UNIVERSITÀ DEGLI STUDI DI MILANO, VIA SALDINI 50, I-20133 MILANO, ITALY. E-MAIL: ROCCA@WIAS-BERLIN.DE AND ELISABETTA.ROCCA@UNIMI.IT

DIMI, UNIVERSITÀ DI BRESCIA, VIA BRANZE 38, I-25100 BRESCIA, ITALY. E-MAIL: RICCARDA.ROSSI@UNIBS.IT

WEIERSTRASS INSTITUTE FOR APPLIED ANALYSIS AND STOCHASTICS, MOHRENSTR. 39, D-10117 BERLIN, GERMANY. E-MAIL: MARITA.THOMAS@WIAS-BERLIN.DE